

STANDARD ARRIVAL CHART

INSTRUMENT (STAR) - ICAO

SEPANG/KL INTERNATIONAL

AIRPORT (WMKK)

TRANSITION ALTITUDE
11 000 FT

RNP 1 (GNSS) RWY 14L, 14R, 15

PUGER 3K KAKAK 3K SAROX 3K
NIREN 3K PULIP 3K GUPTA 3K
 SALAX 3K

TABULAR DESCRIPTION

PUGER THREE KILO ARRIVAL (PUGER 3K)

PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY OVER	COURSE °M	MAGNETIC VARIATION	DISTANCE (NM)	TURN DIRECTION	ALTITUDE (FT)	SPEED LIMIT (KT)	NAVIGATION SPECIFICATION
IF	PUGER	-	-	-	-	-	+FL220	-	RNP 1
TF	SADGI	-	116	-	54.4	-	-	-	RNP 1
TF	KK730	-	108	-	14.7	-	-7000	-	RNP 1
TF	AREBU	-	056	-	11.5	L	+4500	-	RNP 1

NIREN THREE KILO ARRIVAL (NIREN 3K)

PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY OVER	COURSE °M	MAGNETIC VARIATION	DISTANCE (NM)	TURN DIRECTION	ALTITUDE (FT)	SPEED LIMIT (KT)	NAVIGATION SPECIFICATION
IF	NIREN	-	-	-	-	-	+FL220	-	RNP 1
TF	SADGI	-	132	-	45.0	-	-	-	RNP 1
TF	KK730	-	108	-	14.7	L	-7000	-	RNP 1
TF	AREBU	-	056	-	11.5	L	+4500	-	RNP 1

KAKAK THREE KILO ARRIVAL (KAKAK 3K)

PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY OVER	COURSE °M	MAGNETIC VARIATION	DISTANCE (NM)	TURN DIRECTION	ALTITUDE (FT)	SPEED LIMIT (KT)	NAVIGATION SPECIFICATION
IF	KAKAK	-	-	-	-	-	+FL160	-	RNP 1
TF	DAKBA	-	148	-	22.4	-	-	-	RNP 1
TF	AREBU	-	170	-	25.4	R	+4500	-	RNP 1

PULIP THREE KILO ARRIVAL (PULIP 3K)

PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY OVER	COURSE °M	MAGNETIC VARIATION	DISTANCE (NM)	TURN DIRECTION	ALTITUDE (FT)	SPEED LIMIT (KT)	NAVIGATION SPECIFICATION
IF	PULIP	-	-	-	-	-	+FL160	-	RNP 1
TF	KK847	-	208	-	18.0	-	+8000	-	RNP 1
TF	KK896	-	208	-	21.2	-	+6000	-	RNP 1
TF	AREBU	-	236	-	6.4	R	+4500	-	RNP 1

SAROX THREE KILO ARRIVAL (SAROX 3K)

PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY OVER	COURSE °M	MAGNETIC VARIATION	DISTANCE (NM)	TURN DIRECTION	ALTITUDE (FT)	SPEED LIMIT (KT)	NAVIGATION SPECIFICATION
IF	SAROX	-	-	-	-	-	+FL220	-	RNP 1
TF	VEKTO	-	256	-	25.5	-	-	-	RNP 1
TF	KK893	-	258	-	21.8	-	+FL140	-	RNP 1
TF	KK894	-	326	-	12.7	R	-	-	RNP 1
TF	KK895	-	326	-	12.7	-	-	-	RNP 1
TF	KK896	-	326	-	8.2	-	+6000	-	RNP 1
TF	AREBU	-	236	-	6.4	L	+4500	-	RNP 1

CHANGES : REMOVE DAKBA ALTITUDE.