

STANDARD DEPARTURE CHART
INSTRUMENT (SID) - ICAOTRANSITION ALTITUDE
11 000 FTMIRI/MIRI (WBGR)
RWY 02
RNAV (GNSS)ASAKI 1A AROVU 1A BEVDO 1A
BIPAS 1A DOXES 1A DUGEV 1A
ESLAB 1A EXUGO 1A GODOM 1A

TABULAR DESCRIPTION

ASAKI 1A DEPARTURE FOR ROUTE W442

NO.	PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY OVER	COURSE/TRACK °M	DISTANCE (NM)	TURN DIRECTION	ALTITUDE CONSTRAINT	SPEED LIMIT (KT)	NAV SPEC
010	CA	RWY02	-	025°	-	-	1500	-	-
020	DF	ASAKI	-	-	-	L	7000	-	RNAV1

AROVU 1A DEPARTURE FOR ROUTE L517

NO.	PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY OVER	COURSE/TRACK °M	DISTANCE (NM)	TURN DIRECTION	ALTITUDE CONSTRAINT	SPEED LIMIT (KT)	NAV SPEC
010	CA	RWY02	-	025°	-	-	1500	-	-
020	DF	AROVU	-	-	-	L	7000	-	RNAV1

BEVDO 1A DEPARTURE FOR ROUTE W455

NO.	PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY OVER	COURSE/TRACK °M	DISTANCE (NM)	TURN DIRECTION	ALTITUDE CONSTRAINT	SPEED LIMIT (KT)	NAV SPEC
010	CA	RWY02	-	025°	-	-	1500	-	-
020	DF	BEVDO	-	-	-	L	7000	-	RNAV1

BIPAS 1A DEPARTURE FOR ROUTE G580 SOUTHBOUND

NO.	PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY OVER	COURSE/TRACK °M	DISTANCE (NM)	TURN DIRECTION	ALTITUDE CONSTRAINT	SPEED LIMIT (KT)	NAV SPEC
010	CA	RWY02	-	025°	-	-	1500	-	-
020	DF	BETNA	-	-	-	L	-	-	RNAV1
030	TF	BIPAS	-	230°	26.1	R	7000	-	RNAV1

DOXES 1A DEPARTURE FOR ROUTE W422

NO.	PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY OVER	COURSE/TRACK °M	DISTANCE (NM)	TURN DIRECTION	ALTITUDE CONSTRAINT	SPEED LIMIT (KT)	NAV SPEC
010	CA	RWY02	-	025°	-	-	1500	-	-
020	DF	BETNA	-	-	-	L	-	-	RNAV1
030	TF	DOXES	-	211°	26.8	R	7000	-	RNAV1

CHANGES : REMOVE THE SPEED LIMIT (KT) IN TABULAR.