

STANDARD DEPARTURE CHART
INSTRUMENT (SID) - ICAOTRANSITION ALTITUDE
11 000 FTMIRI/MIRI (WBGR)
RWY 02
RNAV (GNSS)

ASAKI 1A AROVU 1A BEVDO 1A
BIPAS 1A DOXES 1A DUGEV 1A
ESLAB 1A EXUGO 1A GODOM 1A

DUGEV 1A DEPARTURE FOR ROUTE W446

NO.	PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY OVER	COURSE/TRACK °M	DISTANCE (NM)	TURN DIRECTION	ALTITUDE CONSTRAINT	SPEED LIMIT (KT)	NAV SPEC
010	CA	RWY02	-	025°	-	-	<u>1500</u>	-	-
020	DF	BETNA	-	-	-	L	-	-	RNAV1
030	TF	DUGEV	-	189°	29.0	L	<u>7000</u>	-	RNAV1

GODOM 1A DEPARTURE FOR ROUTE G580 NORTHBOUND

NO.	PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY OVER	COURSE/TRACK °M	DISTANCE (NM)	TURN DIRECTION	ALTITUDE CONSTRAINT	SPEED LIMIT (KT)	NAV SPEC
010	CA	RWY02	-	025°	-	-	<u>1500</u>	-	-
020	DF	GODOM	-	-	-	R	<u>7000</u>	-	RNAV1

MINIMUM CLIMB GRADIENT (PDG) 5.0% UNTIL 7000 FT DUE TO CTR.

EXUGO 1A DEPARTURE FOR ROUTE W450

NO.	PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY OVER	COURSE/TRACK °M	DISTANCE (NM)	TURN DIRECTION	ALTITUDE CONSTRAINT	SPEED LIMIT (KT)	NAV SPEC
010	CA	RWY02	-	025°	-	-	<u>1500</u>	-	-
020	DF	EXUGO	-	-	-	R	<u>5000</u>	-	RNAV1

MINIMUM CLIMB GRADIENT (PDG) 5.0% UNTIL 5000 FT DUE TO CTR.

ESLAB 1A DEPARTURE FOR ROUTE W449

NO.	PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY OVER	COURSE/TRACK °M	DISTANCE (NM)	TURN DIRECTION	ALTITUDE CONSTRAINT	SPEED LIMIT (KT)	NAV SPEC
010	CA	RWY02	-	025°	-	-	<u>1500</u>	-	-
020	DF	ESLAB	-	-	-	R	<u>5000</u>	-	RNAV1

MINIMUM CLIMB GRADIENT (PDG) 5.0% UNTIL 5000 FT DUE TO CTR.

CHANGES : REMOVE THE SPEED LIMIT (KT) IN TABULAR.