

STANDARD DEPARTURE CHART
INSTRUMENT (SID) - ICAOTRANSITION ALTITUDE
11 000 FTMIRI/MIRI (WBGR)
RWY 20

RNAV (GNSS)

ASAKI 1B AROVU 1B BEVDO 1B
BIPAS 1B DOXES 1B DUGEV 1B
ESLAB 1B EXUGO1B GODOM 1B

TABULAR DESCRIPTION

ASAKI 1B DEPARTURE FOR ROUTE W442

NO.	PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY OVER	COURSE/TRACK °M	DISTANCE (NM)	TURN DIRECTION	ALTITUDE CONSTRAINT	SPEED LIMIT (KT)	NAV SPEC
010	CA	RWY20	-	205°	-	-	<u>1500</u>	-	-
020	DF	BOLAN	-	-	-	R	-	-	RNAV1
030	TF	ASAKI	-	296°	28.4	-	<u>7000</u>	-	RNAV1

AROVU 1B DEPARTURE FOR ROUTE L517

NO.	PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY OVER	COURSE/TRACK °M	DISTANCE (NM)	TURN DIRECTION	ALTITUDE CONSTRAINT	SPEED LIMIT (KT)	NAV SPEC
010	CA	RWY20	-	205°	-	-	<u>1500</u>	-	-
020	DF	BOLAN	-	-	-	R	-	-	RNAV1
030	TF	AROVU	-	276°	26.5	L	<u>7000</u>	-	RNAV1

BEVDO 1B DEPARTURE FOR ROUTE W455

NO.	PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY OVER	COURSE/TRACK °M	DISTANCE (NM)	TURN DIRECTION	ALTITUDE CONSTRAINT	SPEED LIMIT (KT)	NAV SPEC
010	CA	RWY20	-	205°	-	-	<u>1500</u>	-	-
020	DF	BOLAN	-	-	-	R	-	-	RNAV1
030	TF	BEVDO	-	258°	25.7	L	<u>7000</u>	-	RNAV1

BIPAS 1B DEPARTURE FOR ROUTE G580 WESTBOUND

NO.	PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY OVER	COURSE/TRACK °M	DISTANCE (NM)	TURN DIRECTION	ALTITUDE CONSTRAINT	SPEED LIMIT (KT)	NAV SPEC
010	CA	RWY20	-	205°	-	-	<u>1500</u>	-	-
020	DF	ADNOX	-	-	-	-	-	-	RNAV1
030	TF	BIPAS	-	248°	26.8	R	<u>7000</u>	-	RNAV1

DOXES 1B DEPARTURE FOR ROUTE W422

NO.	PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY OVER	COURSE/TRACK °M	DISTANCE (NM)	TURN DIRECTION	ALTITUDE CONSTRAINT	SPEED LIMIT (KT)	NAV SPEC
010	CA	RWY20	-	205°	-	-	<u>1500</u>	-	-
020	DF	ADNOX	-	-	-	-	-	-	
030	TF	DOXES	-	229°	24.9	R	<u>7000</u>	-	RNAV1

CHANGES : REMOVE THE SPEED LIMIT (KT) IN TABULAR.