

STANDARD ARRIVAL CHART
INSTRUMENT (STAR) - ICAO

TRANSITION ALTITUDE
11000 FT

SIBU/SIBU (WBGS)
RNAV (GNSS) RWY 31
NOLUS 1G REDUK 1G LENTU 1G
ELNAL 1G BIPIB 1G ANKUP 1G
PILAX 1G

TABULAR DESCRIPTIONS

NOLUS ONE GOLF ARRIVAL (NOLUS 1G)

PATH TERMINATOR		FLY OVER	COURSE (°M)	DISTANCE (NM)	TURN DIRECTION	ALTITUDE (FT)	SPEED LIMIT (KT)	NAVIGATION SPECIFICATION
IF	NOLUS	-	-	-	-	+5000	-	-
TF	RENIB (IAF)	-	156	25.2	-	+3000	-	RNAV 1
TF	SUGSI (IF)	-	220	5.0	R	+2500	-	RNP APCH

REDUK ONE GOLF ARRIVAL (REDUK 1G)

PATH TERMINATOR		FLY OVER	COURSE (°M)	DISTANCE (NM)	TURN DIRECTION	ALTITUDE (FT)	SPEED LIMIT (KT)	NAVIGATION SPECIFICATION
IF	REDUK	-	-	-	-	+7000	-	-
TF	TAMIG	-	229	13.1	-	+5000	-	RNAV 1
TF	RENIB (IAF)	-	205	25.6	L	+3000	-	RNAV 1
TF	SUGSI (IF)	-	220	5.0	R	+2500	-	RNP APCH

LENTU ONE GOLF ARRIVAL (LENTU 1G)

PATH TERMINATOR		FLY OVER	COURSE (°M)	DISTANCE (NM)	TURN DIRECTION	ALTITUDE (FT)	SPEED LIMIT (KT)	NAVIGATION SPECIFICATION
IF	LENTU	-	-	-	-	+7000	-	-
TF	APPAD	-	248	13.1	-	+5000	-	RNAV 1
TF	RENIB (IAF)	-	229	21.8	L	+3000	-	RNAV 1
TF	SUGSI (IF)	-	220	5.0	-	+2500	-	RNP APCH

ELNAL ONE GOLF ARRIVAL (ELNAL 1G)

PATH TERMINATOR		FLY OVER	COURSE (°M)	DISTANCE (NM)	TURN DIRECTION	ALTITUDE (FT)	SPEED LIMIT (KT)	NAVIGATION SPECIFICATION
IF	ELNAL	-	-	-	-	+7000	-	-
TF	TULMA	-	045	10.0	-	+5000	-	RNAV 1
TF	LEGUG (IAF)	-	068	28.2	R	+3000	-	RNAV 1
TF	SUGSI (IF)	-	040	5.0	L	+2500	-	RNP APCH

BIPIB ONE GOLF ARRIVAL (BIPIB 1G)

PATH TERMINATOR		FLY OVER	COURSE (°M)	DISTANCE (NM)	TURN DIRECTION	ALTITUDE (FT)	SPEED LIMIT (KT)	NAVIGATION SPECIFICATION
IF	BIPIB	-	-	-	-	+7000	-	-
TF	MEGOX	-	067	10.0	-	+5000	-	RNAV 1
TF	LEGUG (IAF)	-	086	32.2	R	+3000	-	RNAV 1
TF	SUGSI (IF)	-	040	5.0	L	+2500	-	RNP APCH

NEW TABULAR