

STANDARD DEPARTURE CHART
INSTRUMENT (SID) - ICAOTRANSITION ALTITUDE
11000 FTSIBU/SIBU (WBGS)
RNAV (GNSS) RWY 13
NOLUS 1A REDUK 1A LENTU 1A
ELNAL 1A BIPIB 1A ANKUP 1A
PILAX 1A

TABULAR DESCRIPTIONS

NOLUS ONE ALFA DEPARTURE (NOLUS 1A)

PATH TERMINATOR	WAYPOINT	FLY OVER	COURSE/TRACK (°M)	DISTANCE (NM)	TURN DIRECTION	ALTITUDE CONSTRAINT	SPEED LIMIT (KT)	RECOMMENDED NAVAIDS	NAVIGATION SPECIFICATION
CA	-	-	130°	-	-	+2000	-	-	RNAV 1
DF	NOLUS	-	-	-	L	+5000	-	-	RNAV 1

REDUK ONE ALFA DEPARTURE (REDUK 1A)

PATH TERMINATOR	WAYPOINT	FLY OVER	COURSE/TRACK (°M)	DISTANCE (NM)	TURN DIRECTION	ALTITUDE CONSTRAINT	SPEED LIMIT (KT)	RECOMMENDED NAVAIDS	NAVIGATION SPECIFICATION
CA	-	-	130°	-	-	+2000	-	-	RNAV 1
DF	TAMIG	-	-	-	L	-	-	-	RNAV 1
TF	REDUK	-	049°	13.1	R	+7000	-	-	RNAV 1

LENTU ONE ALFA DEPARTURE (LENTU 1A)

PATH TERMINATOR	WAYPOINT	FLY OVER	COURSE/TRACK (°M)	DISTANCE (NM)	TURN DIRECTION	ALTITUDE CONSTRAINT	SPEED LIMIT (KT)	RECOMMENDED NAVAIDS	NAVIGATION SPECIFICATION
CA	-	-	130°	-	-	+2000	-	-	RNAV 1
DF	APPAD	-	-	-	L	-	-	-	RNAV 1
TF	LENTU	-	068°	10.0	R	+7000	-	-	RNAV 1

ELNAL ONE ALFA DEPARTURE (ELNAL 1A)

PATH TERMINATOR	WAYPOINT	FLY OVER	COURSE/TRACK (°M)	DISTANCE (NM)	TURN DIRECTION	ALTITUDE CONSTRAINT	SPEED LIMIT (KT)	RECOMMENDED NAVAIDS	NAVIGATION SPECIFICATION
CA	-	-	130°	-	-	+2000	-	-	RNAV 1
DF	TULMA	-	-	-	R	-	-	-	RNAV 1
TF	ELNAL	-	225°	10.0	L	+7000	-	-	RNAV 1

BIPIB ONE ALFA DEPARTURE (BIPIB 1A)

PATH TERMINATOR	WAYPOINT	FLY OVER	COURSE/TRACK (°M)	DISTANCE (NM)	TURN DIRECTION	ALTITUDE CONSTRAINT	SPEED LIMIT (KT)	RECOMMENDED NAVAIDS	NAVIGATION SPECIFICATION
CA	-	-	130°	-	-	+2000	-	-	RNAV 1
DF	MEGOX	-	-	-	R	-	-	-	RNAV 1
TF	BIPIB	-	247°	10.0	L	+7000	-	-	RNAV 1

NEW TABULAR