

STANDARD DEPARTURE CHART
INSTRUMENT (SID) - ICAO

TRANSITION ALTITUDE
11000 FT

SIBU/SIBU (WBGS)
RNAV (GNSS) RWY 31
NOLUS 1C REDUK 1C LENTU 1C
ELNAL 1C BIPIB 1C ANKUP 1C
PILAX 1C

TABULAR DESCRIPTIONS

NOLUS ONE CHARLIE DEPARTURE (NOLUS 1C)

PATH TERMINATOR	WAYPOINT	FLY OVER	COURSE/TRACK (°M)	DISTANCE (NM)	TURN DIRECTION	ALTITUDE CONSTRAINT	SPEED LIMIT (KT)	RECOMMENDED NAVAIDS	NAVIGATION SPECIFICATION
CA	-	-	310°	-	-	+2000	-	-	RNAV 1
DF	NOLUS	-	-	-	R	+5000	-	-	RNAV 1

REDUK ONE CHARLIE DEPARTURE (REDUK 1C)

PATH TERMINATOR	WAYPOINT	FLY OVER	COURSE/TRACK (°M)	DISTANCE (NM)	TURN DIRECTION	ALTITUDE CONSTRAINT	SPEED LIMIT (KT)	RECOMMENDED NAVAIDS	NAVIGATION SPECIFICATION
CA	-	-	310°	-	-	+2000	-	-	RNAV 1
DF	TAMIG	-	-	-	R	-	-	-	RNAV 1
TF	REDUK	-	049°	13.1	L	+7000	-	-	RNAV 1

LENTU ONE CHARLIE DEPARTURE (LENTU 1C)

PATH TERMINATOR	WAYPOINT	FLY OVER	COURSE/TRACK (°M)	DISTANCE (NM)	TURN DIRECTION	ALTITUDE CONSTRAINT	SPEED LIMIT (KT)	RECOMMENDED NAVAIDS	NAVIGATION SPECIFICATION
CA	-	-	310°	-	-	+2000	-	-	RNAV 1
DF	APPAD	-	-	-	R	-	-	-	RNAV 1
TF	LENTU	-	068°	10.0	L	+7000	-	-	RNAV 1

ELNAL ONE CHARLIE DEPARTURE (ELNAL 1C)

PATH TERMINATOR	WAYPOINT	FLY OVER	COURSE/TRACK (°M)	DISTANCE (NM)	TURN DIRECTION	ALTITUDE CONSTRAINT	SPEED LIMIT (KT)	RECOMMENDED NAVAIDS	NAVIGATION SPECIFICATION
CA	-	-	310°	-	-	+2000	-	-	RNAV 1
DF	TULMA	-	-	-	L	-	-	-	RNAV 1
TF	ELNAL	-	225°	10.0	R	+7000	-	-	RNAV 1

BIPIB ONE CHARLIE DEPARTURE (BIPIB 1C)

PATH TERMINATOR	WAYPOINT	FLY OVER	COURSE/TRACK (°M)	DISTANCE (NM)	TURN DIRECTION	ALTITUDE CONSTRAINT	SPEED LIMIT (KT)	RECOMMENDED NAVAIDS	NAVIGATION SPECIFICATION
CA	-	-	310°	-	-	+2000	-	-	RNAV 1
DF	MEGOX	-	-	-	L	-	-	-	RNAV 1
TF	BIPIB	-	247°	10.0	R	+7000	-	-	RNAV 1

NEW TABULAR