

STANDARD DEPARTURE CHART
INSTRUMENT (SID) - ICAO

TRANSITION ALTITUDE
11000 ft

KUANTAN/SULTAN AHMAD
SHAH (WMKD)
RNAV (GNSS) RWY 18
OSTIN 1A VPK 1A
MEVOK 1A OSIKU 1A
DAGAD 1A

TABULAR DESCRIPTION

OSTIN ONE ALFA DEPARTURE (OSTIN 1A)

PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY OVER	COURSE (°M)	DISTANCE (NM)	TURN DIRECTION	ALTITUDE (FT)	SPEED LIMIT (KT)	NAVIGATION SPECIFICATION
CA	-	-	183	-	-	+1000	-	-
DF	ELKOD	-	-	-	L	-	-250	RNAV 1
TF	OSTIN	-	006	18.9	-	+4000	-	RNAV 1

VPK ONE ALFA DEPARTURE (VPK 1A)

PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY OVER	COURSE (°M)	DISTANCE (NM)	TURN DIRECTION	ALTITUDE (FT)	SPEED LIMIT (KT)	NAVIGATION SPECIFICATION
CA	-	-	183	-	-	+1600	-	-
DF	KD212	-	-	-	L	+6000	-	RNAV 1
TF	VPK	-	158	6.3	-	+8000	-	RNAV 1

MINIMUM CLIMB GRADIENT (PDG) OF 5.0% IS REQUIRED UNTIL PASSING 8,000FT DUE TO AIRWAYS LOWER LIMIT.

MEVOK ONE ALFA DEPARTURE (MEVOK 1A)

PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY OVER	COURSE (°M)	DISTANCE (NM)	TURN DIRECTION	ALTITUDE (FT)	SPEED LIMIT (KT)	NAVIGATION SPECIFICATION
CA	-	-	183	-	-	+1600	-	-
DF	MEVOK	-	-	-	R	+7000	-	RNAV 1

MINIMUM CLIMB GRADIENT (PDG) OF 4.5% IS REQUIRED UNTIL PASSING 7,000FT DUE TO AIRWAYS LOWER LIMIT.

OSIKU ONE ALFA DEPARTURE (OSIKU 1A)

PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY OVER	COURSE (°M)	DISTANCE (NM)	TURN DIRECTION	ALTITUDE (FT)	SPEED LIMIT (KT)	NAVIGATION SPECIFICATION
CA	-	-	183	-	-	+1600	-	-
DF	OSIKU	-	-	-	R	+9500	-	RNAV 1

MINIMUM CLIMB GRADIENT (PDG) OF 4.5% IS REQUIRED UNTIL PASSING 9,500FT DUE TO AIRWAYS LOWER LIMIT.

DAGAD ONE ALFA DEPARTURE (DAGAD 1A)

PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY OVER	COURSE (°M)	DISTANCE (NM)	TURN DIRECTION	ALTITUDE (FT)	SPEED LIMIT (KT)	NAVIGATION SPECIFICATION
CA	-	-	183	-	-	+1000	-	-
DF	ELKOD	-	-	-	L	-	-250	RNAV 1
TF	DAGAD	-	322	23.9	L	+8000	-	RNAV 1

NEW TABULAR